



**Request for Quote**  
**LK® Electric Chain Hoists**

**FAX: 937-525-5130**  
**EMAIL: equip.rfq@rmhoist.com**

Company: \_\_\_\_\_

Name: \_\_\_\_\_

Phone: \_\_\_\_\_

E-mail: \_\_\_\_\_

**GENERAL**

Capacity: \_\_\_\_\_

Lift: \_\_\_\_\_

Suspension:  Top hook  Lugmount  Push trolley  
 Motorized trolley  Hand-gearred trolley  Low headroom trolley

Voltage:  460-3-60Hz  230-3-60Hz  208-3-60Hz  
 575-3-60Hz  115-1-60Hz  Other: \_\_\_\_\_

**HOIST AND TROLLEY**

Hoist speed: \_\_\_\_\_

Hoist control:  Single-speed  Two-speed  Variable-speed

Trolley speed: \_\_\_\_\_

Trolley speed control:  Two-speed  Variable speed

Beam flange width: \_\_\_\_\_

Beam type:  Straight track  Curved track: Radius: \_\_\_\_\_

Pendant required?  No  Yes Length: \_\_\_\_\_

Power cord required?  No  Yes Length: \_\_\_\_\_  
 Flat cord  Round cord

**ENVIRONMENT AND DUTY CYCLE**

Location of use:  Indoor  Outdoor  Outdoor under roof

Ambient temperature (Standard is 14-104° F / -10-40° C): \_\_\_\_\_

Hoist duty cycle (ASME/FEM):  H3/1Am  H4/2m

QUOTE REQUIRED BY: \_\_\_\_\_  
NOTES: